

20MP Color UVC USB 3.0 Camera based on Onsemi AR2020 Sensor

Vadzo Falcon-2020CRS is a 20MP USB 3.0 Camera based on Onsemi Hyperlux™ LP AR2020 Sensor. The camera delivers a max resolution of 20MP and Video streaming of 13MP, 4K, 1080p, and 720p. The camera comes with inherent capabilities such as enhanced dynamic range (eDR), excellent Low-Light and NIR Sensitivity. The camera comes with a M12/S-Mount lens holder that supports a 74DFOV lens by default. You shall be able to stream video in UYVY & MJPEG, capture images in UYVY format & MJPEG format, and store in BMP format & JPEG format respectively.

Key Features

- Sensor Model: AR2020 Onsemi Hyperlux™ LP
- Max Resolution: 20MP
- Pixel Size: 1.4 μm x 1.4 μm
- Shutter: Rolling Shutter
- Lens FOV: 74 DFOV
- Compliance: UVC, RoHS 3, REACH



Applications

- **Machine Vision Cameras:** Quality Inspection, Assembly Line Monitoring, Object Recognition and Classification, Surface Inspection, High-Speed Imaging.
- **Smart Surveillance Camera:** Iris Recognition, Day/Night Video Recording, Smart Parking.
- **Medical Devices:** Digital Pathology, Digital Microscopes, Ophthalmic Devices, Fluorescence Imaging.

INDEX

1. Introduction 3

2. Camera Specifications 3

3. Supported Resolutions 5

4. Supported Camera Functions 5

5. USB 3.0 Interface 5

6. Status LED 6

7. General Purpose I/O Lines 6

8. Temperature and Humidity Specifications 6

9. Dimensions..... 7

 Board Top Side – 2D 7

 Board Bottom Side - 2D 7

1. Introduction

Falcon-2020CRS is a UVC-compliant USB 3.0 Fixed-Focus color camera based on Onsemi Hyperlux™ LP AR2020 sensor. The camera is designed to be backward compatible with USB 2.0 as well. The camera incorporates the Onsemi's low-noise CMOS sensor that supports key features like enhanced HDR, Excellent NIR Response @850nm and 940nm, Wake on Motion, and so on.

2. Camera Specifications

General Information	
Product Family	Falcon series
Camera Model	Vadzo Falcon-2020CRS
Sensor	
Sensor	AR2020 CMOS sensor from Onsemi
Sensor Format	1/1.8"
Pixel Size	1.4μm x 1.4μm
Max Resolution	20MP - 5120(H) x 3840(V)
Shutter	Rolling Shutter
Chroma	Color
Camera Data	
Interface	USB 3.2 Gen1 Type C Interface Backward Compatible to USB 2.0
Pixel Depth	8bit / 12bit
Output Format	UYVY and MJPEG
Exposure Control	Manual Control via software & Auto-Exposure
GPIO	6 pins. 1x Digital Input, 1x Digital Output, 3x NC and GND
Camera Hardware	
Lens	S Mount (M12 Standard)
USB connector	Type C

GPIO connector	Connector on-board: Wurth 665306124022 Mating connector: Wurth 665006113322
Power Supply	USB powered
Power Requirement	Max: 1.75 W at 5VDC Min: 1.05 W at 5VDC
Operating Temperature	-30°C to 70°C
Dimension	38mm (L) x 38mm (B) convertible to 32mm (L) x 32mm (B)
Weight	13 Grams (Without Lens)
Camera Software	
Video Resolutions	VGA, HD, Full HD, 4K, 13MP and 20MP
Video formats	UYVY & MJPEG
Still Image Resolutions	VGA, HD, Full HD, 4K, 13MP and 20MP
Image Capture formats	BMP and JPEG
Image Capture Modes	Software trigger
UVC Camera Controls	Brightness, Exposure, Sharpness, Saturation, Gain, Gamma
OS Supported	Windows, Linux.
Conformity	
Conformity	UVC Compliant, RoHS 3, REACH

3. Supported Resolutions

Resolution	Frame Rates (FPS) in USB 3.0		Frame Rates (FPS) in USB 2.0	
	Mode		Mode	
	UYVY	MJPEG	UYVY	MJPEG
640 x 480 (VGA)	120	100	60	60
1280 x 720 (HD)	60	100	16	60
1920 x 1080 (FHD)	60	60	8	60
3840 x 2160 (4K)	15	30	2	15
4208 x 3120 (13MP)	10	20	1	10
5120 x 3840 (20MP)	5	10	1	5

4. Supported Camera Functions

The List of functions supported by the Falcon-2020CRS camera are:

- Resolution Control
- Image Format Setting – UYVY & MJPEG
- Video Format Setting - UYVY & MJPEG
- Image Capture Software Trigger
- Dynamic ROI
- Gain & Exposure
- Brightness
- Anti Flicker – 50Hz/60Hz
- Contrast Control
- Gamma Control
- Saturation Control
- Sharpness Control

5. USB 3.0 Interface

The camera module's USB 3.0 connector is a standard USB Type C connector. It provides a nominal 5 Gbit/s SuperSpeed data transfer connection to supply power to the device and to transmit video data and control signals. The power supply must comply with the Universal Serial Bus 3.0 Specification. The nominal operating voltage is 5 VDC, effective on the camera module's connector. Connection assignments and numbering adhere to the Universal Serial Bus 3.0 standard. USB Certified 3.0 Gen 1 or higher cables to be used. Vadzo does not recommend non-certified USB cables.

6. Status LED

Status LED's indicate the below:

- Red LED indicates Device is powered ON with no Streaming.
- Yellow LED indicates: Camera is currently Streaming.

7. General Purpose I/O Lines

GPIO lines are terminated through Six (6) pin socket connector from Würth Elektronik part number 665306124022. Refer to the below table for GPIO Connector Pin Numbering and Assignments.

Pin	Line	Function
1	Power	Do not use.
2	-	Do not use*
3	-	Do not use*
4	Input1	General Purpose I/O (GPIO) line with 1.8V tolerant directly connected to MCU Preset: Input Line
5	Output1	General Purpose I/O (GPIO) line with 1.8V tolerant directly connected to MCU Preset: Output Line
6	GND	Ground

**Vadzo engineering team shall be able to enable the IOs on the firmware level as per the end user technical requirements under the purview of Vadzo Imaging customisation program.*


Recommended mating connector from Würth Elektronik part number 665006113322.

8. Temperature and Humidity Specifications


Description	Specification
Operating Temperature	-30°C to 70°C
Storage Temperature	-30°C to 70°C
Humidity	20% to 80%, Relative, non-condensing.

9. Dimensions

Board Top Side – 2D



Board Bottom Side - 2D



IMPORTANT NOTICE AND DISCLAIMER

Vadzo Imaging products are sold by description only. Vadzo Imaging reserves the right to change the information in this document, including URL references and/or specifications is subject to change without notice. Customers should obtain the latest relevant information and data sheets before placing orders and should verify that such information is current and complete.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

THIS DOCUMENT IS PROVIDED AS IS WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION, OR SAMPLE.

All liability, including liability for infringement of any proprietary rights, relating to the use of information in this document is disclaimed. No licenses express or implied, by estoppel or otherwise, to any intellectual property rights are granted herein.

All trade names, trademarks, and registered trademarks mentioned in this document are the property of their respective owners and are hereby acknowledged.



Copyright © 2017–2026 Vadzo Imaging. All Rights Reserved.